

Protective covers - VS-PPC-C1-PC67-POBK - 1608155


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Protective cover, IP67, to cover the contact insert in the RJ45 and SC-RJ push-pull panel mounting frames



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 159999
GTIN	4046356159999
Weight per Piece (excluding packing)	21.000 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Mechanical characteristics

Locking type	Push Pull
Insertion/withdrawal cycles	≥ 500
Color	black
Degree of protection	IP65/IP67
Note	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 8.2 Connectors for Outside Environment (Balanced cabling) and Chapter 8.4 Connectors for outside environment (optical fibre) and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

Protective covers - VS-PPC-C1-PC67-POBK - 1608155

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA-GF
Material	Plastic
Cable gland material	PA
O-ring material	NBR
Material housing intermediate seal	NBR
Height	30 mm

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 5.1	27149100
eCl@ss 6.0	27261200
eCl@ss 7.0	27440208
eCl@ss 8.0	27440208
eCl@ss 9.0	27440208

ETIM

ETIM 2.0	EC000241
ETIM 3.0	EC002040
ETIM 4.0	EC002314
ETIM 5.0	EC002314
ETIM 6.0	EC002314
ETIM 7.0	EC002314

UNSPSC

UNSPSC 6.01	30212113
UNSPSC 7.0901	39121712
UNSPSC 11	39121712
UNSPSC 12.01	39121712
UNSPSC 13.2	39121421