

## Cable marker - WMTB HF (40X12)R - 0830407

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Assembly with cable binders, Cable diameter:  $\geq 6$  mm, Lettering field: 40 x 12 mm

### Why buy this product

- The marker has two fastening eyes so that it can be attached to the conductor by means of PKB ... cable binders

### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 715997
GTIN	4046356715997
Weight per Piece (excluding packing)	1,240.000 g
Custom tariff number	39204910
Country of origin	Denmark

### Technical data

#### Dimensions

Length (b)	40 mm
Width (a)	10 mm

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 80 °C
Recommended storage conditions	Storage in a cool and dry place in the original packaging is recommended.

#### General

Color	white
Components	Halogen-free

## Cable marker - WMTB HF (40X12)R - 0830407

### Technical data

#### General

Flammability rating according to UL 94	V0
Material	PUR
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Number of individual labels	1000
Number of individual labels per row	1
RoHS compliant	Yes
Printability	Thermal transfer
Device	5146477 THERMOMARK ROLL 5146723 THERMOMARK ROLL X1 5146231 THERMOMARK X1.2
Ink ribbon	5148007 THERMOMARK-RIBBON 110-WMTB HF
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	96 h
Wipe resistance test result	Test passed
Salt spray test specification	DIN EN 60068-2-11:2000-02
Test duration	96 h
Salt spray testing result	Test passed
Wipe resistance of test specification inscriptions	IEC 61010-1:2010-06
Result	Test passed
Marking mounting type	Assembly with cable binders

#### Standards and Regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V0