



Features

- 0.2 INCH DIGIT HEIGHT.
- LOW CURRENT OPERATION.
- EXCELLENT CHARACTER APPEARANCE.
- I.C. COMPATIBLE.
- MECHANICALLY RUGGED.
- GRAY FACE, WHITE SEGMENT.
- PACKAGE : 600PCS / REEL.
- RoHS COMPLIANT.




Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25(0.01)$ unless otherwise noted.





Absolute Maximum Ratings (TA=25°C)	MDK (InGaAlP)	Unit
Reverse voltage	VR	5 V
Forward current	IF	30 mA
Forward current (peak) 1/10Duty cycle 0.1ms pulse width	iFS	185 mA
Power dissipation	PT	75 mW
Operating temperature	TA	-40 ~ +85 °C
Storage temperature	Tstg	-40 ~ +85 °C

Operating Characteristics (TA=25°C)	MDK (InGaAlP)	Unit
Forward Voltage (Typ.) (IF=10mA)	VF	1.85 V
Forward Voltage (Max.) (IF=10mA)	VF	2.5 V
Reverse Current (VR=5V)	IR	10 uA
Wavelength of Peak Emission (IF=10mA)	λ peak	650 nm
Wavelength of Dominant Emission (IF=10mA)	λ D	635 nm
Spectral Line Full Width At Half-Maximum (IF=10mA)	$\Delta\lambda$	28 nm
Capacitance (VF=0V, f=1MHz)	C	35 pF


Part Number	Emitting Color	Emitting Material	Luminous Intensity (IF=10mA) ucd	Wavelength nm λ P	Description
			min. typ.		
XZDMDK05C2	Red	InGaAlP	8000 30390	650	Common Cathode.Rt. Hand Decimal



❖ MDK




Reflow Soldering Profile For Lead-free SMT Process.




Notes:

1. Maximum soldering temperature should not exceed 260°C.
2. Recommended reflow temperature: 145°C-260°C.
3. Do not put stress to the epoxy resin during high temperatures conditions.

❖ Recommended Soldering Pattern (Units : mm;Tolerance± 0.15)



❖ Tape Specification (Units : mm)



Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: +/-1nm
2. Luminous Intensity: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.