# ZB5FJ2

# flush mounted black selector switch head long handle 2 pos stay put





### Main

| Range of product                | Harmony XB5              |
|---------------------------------|--------------------------|
| Product or component type       | Head for selector switch |
| Device short name               | ZB5                      |
| Bezel material                  | Dark grey plastic        |
| Mounting diameter               | 1.18 in (30 mm)          |
| Head type                       | Built-in-flush           |
| Sale per indivisible quantity   | 1                        |
| Shape of signaling unit head    | Round                    |
| Type of operator                | Stay put                 |
| Operator profile                | Black long handle        |
| Operator additional information | Non padlockable          |
| Operator position information   | 2 positions 90°          |
|                                 |                          |

### Complementary

| 1.46 in (37 mm)  |   |
|--|---|
| 1.46 in (37 mm)  |   |
| 1.81 in (46 mm)  |   |
| 0.07 lb(US) (0.031 kg)   |   |
| 1000000 cycles   |   |
| C3 6 single front mounting C4 6 single and double front mounting C5 5 single front mounting C6 5 single and double front mounting C7 4 single front mounting C8 4 single and double front mounting C11 3 single front mounting C15 1 single front mounting SF1 3 single front mounting |   |
|  | 1.46 in (37 mm)  1.81 in (46 mm)  0.07 lb(US) (0.031 kg)  1000000 cycles  C3 6 single front mounting C4 6 single and double front mounting C5 5 single front mounting C6 5 single and double front mounting C7 4 single front mounting C8 4 single and double front mounting C1 3 single front mounting C11 3 single front mounting C15 1 single front mounting |

### **Environment**

| Protective treatment                  | TH  |  |
|---------------------------------------|---|--|
| Ambient air temperature for storage   | -40158 °F (-4070 °C)  |  |
| Ambient air temperature for operation | -40158 °F (-4070 °C)  |  |
| Overvoltage category                  | Class II conforming to IEC 60536                                |  |
| IP degree of protection               | IP66 IEC 60529<br>IP67 conforming to IEC 60529<br>IP69K<br>IP69 |  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X  |  |
| Resistance to high pressure washer    | 7000000 Pa at 55 °C, distance : 0.1 m                           |  |
| IK degree of protection               | IK03 conforming to IEC 50102                                    |  |

| Standards              | JIS C8201-5-1   |
|------------------------|---|
|                        | EN/IEC 60947-5-1  |
|                        | CSA C22.2 No 14   |
|                        | EN/IEC 60947-5-4  |
|                        | UL 508  |
|                        | EN/IEC 60947-1  |
|                        | JIS C8201-1   |
| Product certifications | RINA  |
|                        | BV  |
|                        | GL<br>DNV   |
|                        | CSA   |
|                        | UL Listed   |
|                        | LROS (Lloyds register of shipping)  |
| Vibration resistance   | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6   |
| Shock resistance       | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |
|                        | 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |

| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
|-----------------------|---------------------------------------|
| Discount Schedule     | CS2                                   |
| GTIN                  | 00785901050094                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 0.05 lb(US) (0.02 kg)                 |
| Returnability         | Yes                                   |
| Country of origin     | FR                                    |
|                       |                                       |

# Packing Units

| Package 1 Height | 0.545 dm |
|------------------|----------|
| Package 1 width  | 0.430 dm |
| Package 1 Length | 0.520 dm |

## Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation           | ☑REACh Declaration  |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | ₽¥Yes   |
| China RoHS Regulation      | China RoHS Declaration  |
| Environmental Disclosure   | Product Environmental Profile   |
| Circularity Profile        | End Of Life Information   |