ZB5FJ4

flush mounted black selector switch head long handle 2 pos return right to left





Main

Range of product	Harmony XB5
Product or component type	Head for selector switch
Device short name	ZB5
Bezel material	Dark grey plastic
Mounting diameter	1.18 in (30 mm)
Head type	Built-in-flush
Sale per indivisible quantity	1
Shape of signaling unit head	Round
Type of operator	Right to left spring return
Operator profile	Black long handle
Operator additional information	Non padlockable
Operator position information	2 positions 90°

Complementary

CAD overall width	1.46 in (37 mm)	
CAD overall height	1.46 in (37 mm)	
CAD overall depth	1.81 in (46 mm)	
Net Weight	0.07 lb(US) (0.031 kg)	
Mechanical durability	1000000 cycles	
Electrical composition code	C3 6 single front mounting C4 6 single and double front mounting	
	C5 5 single front mounting	
	C6 5 single and double front mounting	
	C7 4 single front mounting	
	C8 4 single and double front mounting	
	C11 3 single front mounting	
	C15 1 single front mounting	
	SF1 3 single front mounting	

Environment

Protective treatment	TH	
Ambient air temperature for storage	-40158 °F (-4070 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
Overvoltage category	Class II conforming to IEC 60536	
IP degree of protection	IP66 IEC 60529 IP67 conforming to IEC 60529 IP69K IP69	
NEMA degree of protection	NEMA 13 NEMA 4X	
Resistance to high pressure washer	7000000 Pa at 55 °C, distance : 0.1 m	
IK degree of protection	IK03 conforming to IEC 50102	

Standards	EN/IEC 60947-1
	JIS C8201-5-1
	UL 508
	EN/IEC 60947-5-1
	CSA C22.2 No 14
	EN/IEC 60947-5-4
	JIS C8201-1
Product certifications	RINA
	LROS (Lloyds register of shipping)
	DNV
	CSA
	GL
	BV
	UL Listed
Vibration resistance	5 gn (f= 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC
	60068-2-27
	50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC
	60068-2-27

Ordering and shipping details

Category	22467 - PUSHBUTTONS,22MM(PLASTIC) NEW
Discount Schedule	CS2
GTIN	03606481340269
Nbr. of units in pkg.	1
Package weight(Lbs)	0.05 lb(US) (0.02 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	2.15 in (5.45 cm)	
Package 1 width	1.69 in (4.3 cm)	
Package 1 Length	2.05 in (5.2 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	