## ZB5FK1343

# flush mounted red illuminated selector switch head 3 pos stay put





#### Main

| Range of product              | Harmony XB5                          |
|-------------------------------|--------------------------------------|
| Product or component type     | Head for illuminated selector switch |
| Product compatibility         | Integral LED                         |
| Device short name             | ZB5                                  |
| Bezel material                | Dark grey plastic                    |
| Mounting diameter             | 1.18 in (30 mm)                      |
| Head type                     | Built-in-flush                       |
| Sale per indivisible quantity | 1                                    |
| Shape of signaling unit head  | Round                                |
| Type of operator              | Stay put                             |
| Operator profile              | Red standard handle                  |
| Operator position information | 3 positions +/- 45°                  |
|                               |                                      |

#### Complementary

| Device presentation         | Basic element                                           |  |
|-----------------------------|---------------------------------------------------------|--|
|                             | M4 4 single and double front mounting integral LED      |  |
| ·                           | MF1 2 single front mounting integral LED                |  |
|                             | M10 2 single front mounting integral LED                |  |
|                             | M6 2 single front mounting integral LED and transformer |  |
| Electrical composition code | M3 4 single front mounting integral LED                 |  |
| Mechanical durability       | 1000000 cycles                                          |  |
| Net Weight                  | 0.07 lb(US) (0.03 kg)                                   |  |
| '                           | , ,                                                     |  |
| CAD overall depth           | 1.81 in (46 mm)                                         |  |
| CAD overall height          | 1.46 in (37 mm)                                         |  |
| CAD overall width           | 1.46 in (37 mm)                                         |  |
|                             |                                                         |  |

#### Environment

| Protective treatment                  | TH                                                                                                                                      |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Ambient air temperature for storage   | -40158 °F (-4070 °C)                                                                                                                    |
| Ambient air temperature for operation | -40158 °F (-4070 °C)                                                                                                                    |
| Overvoltage category                  | Class II conforming to IEC 60536                                                                                                        |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67<br>IP69<br>IP69K                                                                                   |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X                                                                                                                      |
| Resistance to high pressure washer    | 7000000 Pa at 55 °C, distance : 0.1 m                                                                                                   |
| IK degree of protection               | IK03 conforming to IEC 50102                                                                                                            |
| Standards                             | EN/IEC 60947-1<br>CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-5<br>UL 508<br>EN/IEC 60947-5-4<br>JIS C8201-5-1<br>JIS C8201-1 |

| Product certifications | GL                                                                         |
|------------------------|----------------------------------------------------------------------------|
| Troduct certifications |                                                                            |
|                        | DNV                                                                        |
|                        | CSA                                                                        |
|                        | LROS (Lloyds register of shipping)                                         |
|                        | BV                                                                         |
|                        | UL Listed                                                                  |
|                        | RINA                                                                       |
| Vibration resistance   | 5 gn (f= 2500 Hz) conforming to IEC 60068-2-6                              |
| Shock resistance       | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC |
|                        | 60068-2-27                                                                 |
|                        | 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC |
|                        | 60068-2-27                                                                 |

### Ordering and shipping details

| Category              | 22467 - PUSHBUTTONS,22MM(PLASTIC) NEW |
|-----------------------|---------------------------------------|
| Discount Schedule     | CS2                                   |
| GTIN                  | 00785901051169                        |
| Nbr. of units in pkg. | 1                                     |
| Package weight(Lbs)   | 0.05 lb(US) (0.02 kg)                 |
| Returnability         | Yes                                   |
| Country of origin     | FR                                    |

## Packing Units

| Unit Type of Package 1 | PCE               |
|------------------------|-------------------|
| Package 1 Height       | 2.15 in (5.45 cm) |
| Package 1 width        | 1.69 in (4.3 cm)  |
| Package 1 Length       | 2.05 in (5.2 cm)  |

## Offer Sustainability

| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                     |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation           | REACh Declaration                                                                                                                                                                                                                         |
| REACh free of SVHC         | Yes                                                                                                                                                                                                                                       |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration                                                                                                                                                           |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                       |
| Mercury free               | Yes                                                                                                                                                                                                                                       |
| RoHS exemption information | ₫Yes                                                                                                                                                                                                                                      |
| China RoHS Regulation      | China RoHS Declaration                                                                                                                                                                                                                    |
| Environmental Disclosure   | Product Environmental Profile                                                                                                                                                                                                             |
| Circularity Profile        | ☑ End Of Life Information                                                                                                                                                                                                                 |
|                            |                                                                                                                                                                                                                                           |