## MALLORY Mallory Sonalert Products, Inc. Part #: Sales Outline Drawing Revision:

ZT028LAFP1R C

^		 1	4 .	
- n	$\sim$	 $\sim$	+1/	nc:
JU	EL	 La		HIS.
_		 		ns:

Sound Level Category	Loud		
Mode of Operation	Fast Pulse Sound and Light @ 10 PPS		
Lens Color	Opaque White		
LED Color	RED		
LED Mode of Operation	FLASH 10PPS		
Voltage Rating	20 to 28 VAC/DC		
Frequency	3900 ± 500 Hz		
Loudness @ 2 FT	85 to 95 dB(A) Typ.		
Current Draw	40mA MAX		
Housing Material	6/6 Nylon, Color: Black		
Front Cap Material	6/6 Nylon, Color: Opaque White		
Storage Temperature	-40° to +80° C		
Operating Temperature	-30° to +65° C		
Panel Mounting	Recommended hole size is 22.5 mm. Thread front will fit standard 22.5mm hole.		
Knurled Nut	Used to attach part to panel. The max recommended torque is 10 in-lbs.		
Weight (Typical)	28 g		
NEMA 3R,4X, & 12	MA 3R,4X, & 12 Approved with use of included gasket.		
Options	Please contact factory.		

